

ADTRAXION Xs PLAYER

Small sized Adtraxion Player, providing great performance

The Adtraxion Xs Player is a fully dedicated digital signage player, which is part of the Adtraxion solution. It is characterized by its small form factor, while meeting the most demanding digital signage applications.

The available optional expansions and diverse storage solutions offer maximum flexibility. In this way it is possible to adapt the Adtraxion Xs Player to the project requirements.



MAIN BENEFITS

- **24/7 operation**
- **Energy saving mode**
- **Robust and reliable**
- **Fanless design**
- **Diverse storage solutions**
- **Small form factor**
- **Extreme low power consumption**
- **Supports many content formats**
- **WiFi (optional)**
- **Live TV (optional)**

ADTRAXION Xs PLAYER

Energy efficient

The Adtraxion Xs Player is an extremely energy efficient device. It uses considerably less energy while performing, and automatically switches to a low power mode when no Adtraxion schedule is active. While in low power mode it also signals the display to turn off, making the display also a less power consuming device.

Watchdog

For reliable operation, the watchdog functionality is designed in both the hard- and software configuration, to secure 24/7 operation.

Monitoring

The Player has an extensive monitoring on board. Its status, temperature, load and memory usage can be remotely monitored.

Specifications

Environmental specifications

Power Supply	AC Input: 100V ~ 240V, 50~60Hz
Operating temperature	0~40°C
Humidity	90% relative humidity (40°C non-condensing)
Dimension	166x48x157 mm

Display support

Decoding interface	DVI-I
Resolution	Up to 1920x1200

I/O

Network	Two RJ-45 IEEE 802.3 10/100/1000 Wireless IEEE 802.11b/g (optional)
Video	DVI-I
Audio	Analogue stereo
Serial (RS232)	Two serial ports
USB	Four USB ports, USB version 2.0 compliant
TV tuner (optional)	Global supported twin tuner for analogue RF or DVB-T* support

Storage capacity

Capacity	Dependable on storage device
----------	------------------------------

Accessories

Power cable	EU
Mounting	L-type holder
Video	DVI to VGA converter

Format support

Video formats	
MPG	MPEG-1 MPEG-2 - MP@ML (max. 10 Mbps)
WMV	WMV9 - (max. 8 Mbps)
Audio formats	
MP3	MPEG-1 Audio Layer 2
WAV	PCM 44KHz, 16-bit (stereo)
WMA	WMA 9 (stereo)
Image formats	
JPG	JPEG (RGB)**
BMP	Windows Bitmap (RGB, RGBA, RLE)**
GIF	Graphics Interchange Format (up to 1920x1200)
PNG	Portable Network Graphics (RGB, RGBA)**
Animation formats	
SWF	Flash 10
WEB	Microsoft Silverlight 2
PPT	PowerPoint 97/2003
PPTX	PowerPoint 2007
Streaming formats	
UDP-MPEG-2 SPTS	
Other formats	
RSS 2.0 feeds	
Text files (ANSI/Unicode)	
URL/WEB	

* Only free-to-air channels ** Up to 32-Bits and 1920x1200 resolution

Ordering information

	160 GB HDD	Wi-Fi	TV RF Tuner	
			RF	DVB-T*
ADX8001 - Adtraxion Xs Player	✓			
ADX8002 - Adtraxion Xs Player wireless solution	✓	✓		
ADX8003 - Adtraxion Xs Player LiveTV solution	✓		✓	✓

On request the Adtraxion Xs Player can be delivered with SSD instead of the 160GB HDD

ADTRAXION
S Y S T E M S

www.adtraxion.com

Specifications are subject to change without notice. Trademarks owned by Adtraxion Systems.

- All rights reserved V28-09-09 -