

ADTRAXION

As Player

Palm-sized Adtraxion Player,
providing great performance



The Adtraxion As Player is a robust and reliable digital signage player.

Its fan-less design is ideal for users who require a compact and rugged platform for entry-level digital signage applications.

Main benefits

- > 24/7 operation
- > Robust and reliable
- > Standard 4 Year warranty
- > Fanless design
- > Low power consumption
- > Ultra compact size
- > VESA mountable
- > Supports many content formats

Adtraxion As Player



Watchdog

For reliable operation, the watchdog functionality is designed in both the hardware and the software configuration, to secure 24/7 operation.

Monitoring

The player has an extensive monitoring on board. Its status, temperature, load and memory usage can be remotely monitored.

High level of network security

To prevent unauthorized network activities different levels of security are implemented. The dedicated firewall settings will prevent unauthorized network access. With its encrypted communication and propriety protocol, the Adtraxion As Player is even more safe and secure.

Specifications

Mechanical

Dimensions 133.8 x 43.1 x 94.2 mm
Weight 0.7 kg

Environment

Operating Temperature 0 ~ 40° C (32 ~ 104° F) with
0.7m/s air flow
Storage Temperature -40 ~ 85° C
Relative Humidity 95% @ 40° C (non-condensing)

Power

Power Type ATX
Power Input Voltage 12 Vdc
Minimum Power Input 12 V, 1.5 A
Power Adaptor AC to DC, DC12 V/3 A, 36 W
Power Consumption Average: 9.12 W - Maximum: 10.80 W

Graphics

Interface CRT interface, up to 1400 x 1050 (SXGA)

I/O Interface

VGA Yes
Serial Ports 2 x RS-232
USB Interface 4 x USB ports, USB 2.0 Compliant
Lan 1 x 10/100/1000 Ethernet controller

Storage capacity

HDD capacity 160 GB HDD

Warranty

Warranty 4 Years (excluding moving parts)

* Image files should not exceed 1MB in file size or 1920 pixels wide by 1080 pixels tall. We strongly recommend uploading images at the size you wish for them to display on the screen.

Supported Media Formats

Video formats	
MPG	MPEG layer 1, 2 (MP@HL - max. 10 Mbps)
WMV	WMV9 (max. 8 Mbps)
MP4	H264/AVC - HP@L4.0/4.1 (max. 5 Mbps)
Audio formats	
MP3	MPEG-1 Audio Layer 2
WAV	PCM 44KHz, 16-bit (stereo)
WMA	WMA 9 (stereo)
AC3	Dolby Digital (2.0, 2.1 and 5.1)
MP4	AAC-LC (stereo)
Image formats	
JPG	JPEG (RGB)*
BMP	Windows Bitmap (RGB, RGBA, RLE)*
GIF	Graphics Interchange Format*
PNG	Portable Network Graphics (RGB, RGBA)*
Animation formats	
SWF	Flash 10
PPTX	PowerPoint 2010
WEB	Microsoft Silverlight 5
Streaming formats	
UDP SPTS	MPEG-2 (SD) (max. 8Mbit/sec) H264/AVC1 (HP@L4.0/4.1) (max. 5 Mbit/sec)
ASF/URL	WMV9/VC-1 TCP/UDP streaming support through RTSP/MMS protocol (max. 10Mbit/sec).
Audio	MPEG-1 Audio Layer II AAC LC (Stereo) AC3 (Dolby Digital 2.0, 2.1 and 5.1)
Other formats	
	Live RSS 2.0 Text files (ANSI/Unicode) URL/WEB

Ordering information

ADXAS01

Adtraxion As Player

ADTRAXION
awareness on the spot
www.adtraxion.com

Specifications are subject to change without notice. Trademarks owned by Adtraxion Systems. All rights reserved V01-05-12.